


Introducing...

E-Z-Set Polymer Detectable Warning Panels



At 26 lbs. polymer concrete panels are easily handled by one person



Two panels form a 2' x 4' truncated dome surface




Five ABS anchors secure panels in place

Detectable Warning Systems, Inc. now offers the ultimate solution for the required truncated dome detectable warning surface in curb ramps and at hazardous vehicular areas. These glass fiber polymer cement panels are molded in the square pattern, now recommended by the Access Board and FHWA. The domes allow improved access for wheeled mobility aids.

- **Great for new construction projects**
- **Designed to be placed into wet concrete during ramp construction**
- **Lightweight, easy to use panels**
- **Installation process is simple and easy and can be accomplished by one person in 5-10 minutes**
- **No adhesives, sealants, or curing time needed**
- **Incredibly strong & durable**
- **Five-year manufacturer's limited warranty against defects in materials and workmanship**

DETECTABLE WARNING SYSTEMS

It's Easy...Lightweight, easy to use composite panels are 1/2" thick and weigh only 26 pounds each. The panels are designed to be placed into wet concrete during ramp construction. The simple anchor design eliminates the need for adhesive, sealants, and curing time. Texturing on both the dome surface and the surrounding areas provide slip-resistance for pedestrian traffic.



It's Strong...Incredibly strong and durable, the lightweight panels are perfectly molded from polymer cement, the composite material is equivalent to 8,000 PSI concrete. It is also fireproof with "0" flame spread, allowing it to be used in subways and other interior locations.



Detectable Warning Systems

Detectable Warning Systems has been providing polyurethane detectable warning mats since 1994, with thousands of successful application throughout the United States. It maintains an extensive distribution system through local dealers with 32 locations in the United States including Alaska and Hawaii.

Minutes to Install-Years of Service

The installation process is simple and easy and can be accomplished by one person in 5-10 minutes. No hassle, no worries. The panels are simply tapped into wet concrete and anchors inserted.

Replacement

In the unlikely event that panel is damaged, it can be easily removed and replaced with a new unit at minimal expense.

Colors

Offered in yellow and brick red. Custom colors available by special order.

Five-Year Warranty

These panels carry a five-year manufacturers limited warranty against defects in workmanship and materials.



Please contact us for information, samples or the location of the distributor nearest to you.

**Detectable Warning Systems, Inc.
P.O. Box 17685
Anaheim, CA 92817-7685
866-999-7452
detectable@aol.com
www.detectable-warning.com**

DETECTABLE



WARNING SYSTEMS